

6200 Series EPDM Rubber Foam

This single sided closed cell foam is resistant to UV rays, weathering and does not allow ingress of air, dust, moisture or water.

Suitable for:

- Construction/Fabrication
- Glass & Glazing
- Rail networks/Boat building
- Die cut gasket applications
- Thermal & Acoustic barriers
- Insulation for Solar Panel Systems

Features & Benefits:

- Provides sealing properties against air, dust, water & moisture
- Ozone, weather & heat resistant attributes
- High temperature performance
- Environmental Protection: CFC, Halogen & HCFC Free
- Flame Resistance (>3mm) Standard: FMVSS302
- REACH & RoHS compliant to (EU) 2015/863 or 2018/2005 EC
- Thicknesses (mm): 1.6, 3.2, 4.8, 6.4, 9.5 & 12.7
- Halogen free
- Can be used as an electrolysis barrier tape as electrically non conductive material in general applications but at high voltage electricity applications it could be conductive



Custom widths available from 6mm - 1000mm

All pricing quoted is per roll & excluding GST, based on full carton quantity. Subject to normal FIS terms. Purchaser is responsible for determining suitability of this product for their application. For more detailed information on any of our products please refer to our website The above information is given in good faith for guidance and not specification purposes.

www.stylustapes.com.au

ADELAIDE | BRISBANE | MELBOURNE | PERTH | SYDNEY | AUCKLAND



























